



Wireless Security and Life-Safety Sensing Products

Compatibility: **319.5 MHz** **UTC®, Interlogix®, GE®, ITI®, Qolsys®**
345 MHz **Honeywell® and 2GIG®**

Experienced | The new wireless sensor company that has been making wireless security products for over 30 years.

Security Innovation | Continuous Product Improvement on our security products has resulted in 9 U.S. Patents and ground-breaking development of encrypted security systems.

Engineering and Development Partner | MaxOut™ Technology has been behind many of the security products used for residential, commercial, and high security today.

MINI DOOR / WINDOW SENSOR

- Signals: supervisory, tamper, and low battery
- Dual tamper; sensor and case for added security
- Effective with vertical or horizontal mount, even on steel surfaces
- Replaceable extra long-life batteries: 2-3VDC lithium coin-cell

NEW! Mini Door /Window sensor [brown sensor and magnet covers.](#)
Enclosure cover replacement kit contains 5 each, brown: sensor covers, sensor



2.25"x 1"x .5"

RECESSED DOOR / WINDOW SENSOR

- New, high powered micro processor chip for exceptional range
- Small, narrow switch package
- Exceptional RF performance
- Replaceable extra long-life lithium battery

319.5 MHz: UTC®, Interlogix®, GE®, ITI®, and Qolsys®



2.25"x .75"

TOTAL WINDOW SENSOR

- LED activates on shock activation and goes out on restore
- Adjustable potentiometer for shock sensitivity
- Vertical or horizontal mount. Superior RF performance, even on steel surfaces
- Replaceable extra long-life batteries: 2-3VDC lithium coin cell

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®
345 MHz. Honeywell® and 2GIG®



2.25"x 1"x .5"

CEILING MOUNT WIRELESS PIR

- Panoramic, 360° coverage
- Advanced, sensitive Micro-processor for superior detection and signal
- Wall tamper
- Two replaceable extra long-life Lithium batteries

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®



3" x 1.4"

Wireless Security and Life-Safety Sensing Products

Compatibility: **319.5 MHz** UTC®, Interlogix®, GE®, ITI®, Qolsys®
345 MHz Honeywell® and 2GIG®

KEYFOB CONTROL

The RF-Keyfob-319-NN is a wireless hand-held device is used to turn on and off a 319.5 MHz alarm system. Allows arming, disarming, panic activation, and light control. The sensor is powered by a replaceable 3-VDC, Lithium coin-cell battery.



2.32" x 1.5" x .4"

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

KEYFOB PANIC

Wireless hand-held portable panic alert, sending an alarm signal when programmed into a 319.5 MHz control panel. False alarm feature; 2-second button hold to send signal to the panel and onto central station for assistance. 2-second hold prevents false alarm from unintentional button press/bump. Replaceable 3-VDC, Lithium coin-cell battery.



2.32" x 1.5" x .4"

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

LONG-RANGE PANIC

- Small, light-weight, wireless handheld or mounted alert device.
- Alert for Police, medical reporting, silent alarm reporting and /or local signals only
- Powerful, with long-range capability
- Includes removable belt clip and lanyard clip. Optional under desk/counter mounting bracket



3" x 2" x .7"

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

MINI RATE-OF-RISE HEAT DETECTOR

- Electronic processing to detect and report rising heat conditions
- Fixed temperature; 135°F (57°C) or 200°F (93°C), depending on the model
- Ceiling mount with very small footprint, tamper switch
- Extra long-life battery




2.25" x 1.5"

319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®
345 MHz. Honeywell® and 2GIG®

WIRELESS CONVERSION MODULES

Both the RF-CHW-8-NN (8 Zone,) and RF-CHW-16-NN (16 Zone,) modules allow the conversion of up to 8 or 16 hardwire security zones to compatible 319.5 MHz wireless control panels such as UTC®/Interlogix®, GE®, and Qolsys®. Support both hardwire magnetic contacts and powered devices.

8 Zones or 16 Zones



319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

7.75" x 4.25" x 1.25"

ENCLOSURE TAMPER SWITCH—S-ET

- Adjustable plunger length. Closed-loop with built-in automatic service shunt
- For use as a wall and or cover tamper
- UL 1076 Approved
- Compare to Sentrol 3025 Tamper Switch
- Includes mounting hardware



2" x 1" x .75"