

Wireless Keyfob Panic

- Simple 1 step “learn-in” for 319.5 MHz wireless control panels.
- Lightweight and compact:
2.37” L x 1.5” W x .4” D
- Silicone, non-slip button offers a secure feel—easy to find on the fob, even in the dark.
- LED ring activates when function button is pressed. Indicating a signal has been sent.
- Long-life battery—5 years, easy to replace.
- Built with MaxOut™ Technology for maximum Radio Frequency (RF) security sensor reliability. MaxOut high performance sensors deliver the maximum signal strength and range.

Regulatory:

- FCC compliant.
- Canadian IC compliant.

The RF-Keyfob Panic-319 is a wireless handheld device that is used as a portable panic, life safety device programmed into a 319.5 MHz control panel.

False alarm feature; 2-second button hold to send signal to the panel and onto central station for assistance. 2-second hold prevents false alarm from unintentional button press/bump.

The keyfob is powered by a replaceable 3-VDC, Lithium coin-cell battery.



Specifications

Model Number and Ordering:	RF-FOB-PANIC-319-NN
RF Frequency:	319.5 MHz
Compatibility:	319.5 MHz: UTC®, Interlogix®, GE®, and ITI® Learn-Mode panels and receivers
Battery Type: (Requires 1)	3-VDC Lithium Coin-Cell Battery, Varta or Panasonic CR2032
Operating Temperature Range:	32 to 120°F (0 to 49°C) -30 to 140°F (-34 to 60°C)
Storage Temperature Range:	
Relative Humidity:	95% Non-Condensing
Dimensions (L x W x D):	2.37 in. x 1.5 in. x 0.40 in.

Regulatory

FCC: 2ABBZ-RF-FOB-PANIC

IC: 11817A-RFFOBPANIC

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.