

## Wireless Security and Life-Safety Sensing Products

Professional Sensing Products for Professional Security Dealers

**Experience** - The new wireless sensor company that has been making wireless security products for over 30 years.

**Proven Security Innovation** - Continuous Product Improvement on our security products has resulted in 9 U.S. Patents and ground-breaking development of encrypted security systems.

**Trusted Engineering and Development Partner** - MaxOut™ Technology has been behind many of the security products used for residential, commercial, and high security today.

### DOOR / WINDOW SENSOR - MINI

- Signals: supervisory, tamper, and low battery.
- Dual tamper; sensor and case for added security.
- Effective with vertical or horizontal mount, even on steel surfaces.
- Replaceable extra long-life batteries: 2-3VDC lithium coin-cell.

**RF-CMDWS-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**RF-CMDWS-345-NN** 345 MHz. Honeywell® and 2GIG®

**RF-CMDWS-433-NN** 433 MHz. DSC®



2.25"x 1"x .5"

### HIGH SECURITY DOOR / WINDOW SENSOR

The most secure wireless sensors available! The only wireless sensor utilizing the award-winning all metal switch technology from Magnasphere Corporation; impervious to contact welding and resistant to magnetic tamper and defeat. The patented MSSRFS series sensors provide the strongest FCC allowable output signal with a 14+ year battery life.

**MSS-RFS-100** 319.5 MHz: UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**MSS-RFS-200** 345 MHz: Honeywell® and 2GIG®

**MSS-RFS-300** 319.5 MHz: Napco®



3"x 1"x .95"

### TOTAL WINDOW SENSOR - MINI

- LED activates on impact activation and goes out on restore.
- Adjustable potentiometer for impact sensitivity.
- Effective with vertical or horizontal mount.
- Replaceable extra long-life batteries: 2-3VDC lithium coin cell.
- Superior RF performance, even on steel surfaces

**RF-SHK-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**RF-SHK-345-NN** 345 MHz. Honeywell® and 2GIG®

**RF-SHK-433-NN** 433 MHz. DSC®



2.25"x 1"x .5"

### WIRELESS CONVERSION MODULES

Both the RF-CHW-8-NN (8 Zone,) and RF-CHW-16-NN (16 Zone,) modules allow the conversion of up to 8 or 16 hardwire security zones to compatible 319.5 MHz wireless control panels such as UTC®/Interlogix®, GE®, and Qolsys®. The modules support both hardwire magnetic contacts and powered devices (12VDC,) such as motion detectors.

**RF-CHW-8-NN** 8 Zone, 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**RF-CHW-16-NN** 16 Zone, 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®



7.75"x 4.25"x 1.25"

**KEYFOB CONTROL**

The RF-Keyfob-319-NN is a wireless hand-held device is used to turn on and off a 319.5 MHz alarm system. Allows arming, disarming, panic activation, and light control. The sensor is powered by a replaceable 3-VDC, Lithium coin-cell battery.

**RF-KEYFOB-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®



2.32"x 1.5"x .4"

**KEYFOB PANIC**

Wireless hand-held device that is used as a portable panic alert, sending an alarm signal when programmed into a 319.5 MHz control panel. False alarm feature; 2-second button hold to send signal to the panel and onto central station for assistance. 2-second hold prevents false alarm from unintentional button press/bump. Replaceable 3-VDC, Lithium coin-cell battery.

**RF-FOB-PANIC-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®



2.32"x 1.5"x .4"

**PANIC**

- Small and light-weight, wireless handheld or mounted device, that when pressed sends a signal to the alarm panel.
- Alert for Police, medical reporting, silent alarm reporting and /or local signals only.
- Powerful, with long-range capability.
- Includes removable belt clip and lanyard clip.
- Optional under desk/counter mounting bracket.

**RF-PANIC-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®



3"x 2"x .7"

**RATE-OF-RISE HEAT DETECTOR - MINI**

- Electronic processing to detect and report rising heat conditions.
- Fixed temperature; 135°F (57°C) or 200°F (93°C), depending on the model.
- Ceiling mount with very small footprint, tamper switch.
- Extra long-life battery.

**RF-ROR-135-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**RF-ROR-135-345-NN** 345 MHz. Honeywell® and 2GIG®

**RF-ROR-200-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**RF-ROR-200-345-NN** 345 MHz. Honeywell® and 2GIG®



2.25"x 1.5"

**WATER SENSOR**

Wireless Water Sensor is the ideal "peace of mind" sensor to add to a security system. If the possibility of unwanted water exists from: toilet overflow, hose leak, sump pump failure, or pipe leak—the Water Sensor is on guard to alert of water accumulation and damage. Detects water as little as 1/32".

**C-RF-WATER-319-NN** 319.5 MHz. UTC®, Interlogix®, GE®, ITI®, and Qolsys®

**C-RF-WATER-345-NN** 345 MHz. Honeywell® and 2GIG®



1.77"x .7"x .38"

2.5"x 1"x .5"