

Mini Door / Window Sensor

Wireless, Supervised Sensor

- Easy to install.
- Easy to “Learn” into 319.5 MHz wireless control panels.
- Compact size: 2 1/4” L x 1” W x 1/2” D
- Signals: supervisory, tamper, and low battery.
- Dual tamper; sensor and case for added security.
- Effective with vertical or horizontal mount.
- Replaceable extra long-life batteries: 2-3VDC lithium coin cell.
- Smaller and narrow switch package.
- Superior RF range and performance, even on steel surfaces.
- Wireless sensors and detectors built with MaxOut™ Technology for maximum Radio Frequency (RF) security sensor reliability. MaxOut high performance sensors deliver the maximum FCC allowable output for maximum signal strength and range.

The Mini Door/Window Sensor is a supervised, wireless sensor that detects the opening and closing of doors or windows. New, high-powered Microchip delivers exceptional range; 360° with no dead spots or signal drop-offs.

Patented design with an isolated antenna 1/8” above board and separated from batteries for superior RF performance and transmission efficiency. Reduced interference from metal door and window frames. Reduced battery energy draw lengthens the battery life.



Specifications

| | |
|------------------------------|---|
| Model Number: | RF-CMDWS-319-NN, 319.5 MHz |
| | RF-CMDWS-345-NN, 345 MHz |
| RF Frequency: | 319.5 MHz and 345 MHz |
| Compatibility: | UTC®, Interlogix®, GE®, ITI® and Qolsys®, Learn Mode Control Panels |
| Battery Type: (Requires 2) | 3-VDC Lithium Coin-Cell Battery, Varta or Panasonic CR2032 |
| Operating Temperature Range: | 32 to 120°F (0 to 49°C) |
| Storage Temperature Range: | -30 to 140°F (-34 to 60°C) |
| Relative Humidity: | 95% Non-Condensing |
| Dimensions (L x W x D): | 2.25 in. x 1.0 in. x 0.50 in. |

Regulatory

FCC
IC CANADA
Compliant

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: 2ABBZ-RF-CMDWS-319

IC: 11817A-RFCMDWS319

FCC ID: 2ABBZ-RF-CMDWS-345

IC: 11817A-RFCMDWS345

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.