Wireless Keyfob System Control

Arm-Disarm-Panic-Lights-On

- Easy to install.
- Simple 3-step "learn-in" for 319.5 MHz wireless control panels.
- Lightweight and compact: 2.37" L x 1.5"
 W x .4" D
- LED activates when function button is pressed.
- Long-life battery–5 years, simple to replace.
- Built with MaxOut[™] Technology for maximum Radio Frequency (RF) security sensor reliability. MaxOut high performance sensors deliver the maximum FCC allowable output for maximum signal strength and range.

Regulatory:

- FCC compliant.
- Canadian IC compliant.

The RF-Keyfob is a wireless handheld device that is used to turn on and off the alarm system.

Allows arming, disarming, panic activation, and lighting; if configured. The sensor is powered by a replaceable 3-VDC, Lithium coin-cell battery.

The RF-Keyfob provides the user:

- Arm-Away Mode all devices active.
- Arm-Stay Mode interior devices off.
- Panic Activation.
- Lights Activate if control panel supports.





Specifications

Model Number: RF-Keyfob-319-NN 319.5 MHz

RF-Keyfob-345-NN 345 MHz

RF Frequency: 319.5 MHz

345 MHz

Compatibility: 319.5 MHz UTC®, Interlogix®, GE®, ITI® and Qolsys®

345 MHz Honeywell® and 2GIG®

Battery Type: (Requires 2) 3-VDC Lithium Coin-Cell Battery, Varta or Panasonic CR2032

Operating Temperature Range: 32° to 120°F (0° to 49°C)

Storage Temperature Range: -30° to 140°F (-34° to 60°C)

Relative Humidity: 95% Non-Condensing

Dimensions (L x W x D): 2.37 in. x 1.5 in. x 0.40 in.

Regulatory

FCC: 2ABBZ-RF-KEYFOB-319

2ABBZ-RF-KEYFOB-345

IC: 1817A-RFKEYFOB319

11817A-RFKEYFOB345

This device complies with part 15 of the FCC Rules. Operation is subject

to the following two conditions:

(1)This device may not cause harmful interference, and

(2) This device must accept any interference received, including interfer-

ence that may cause undesired operation.

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-

003 du Canada.

