

Experience - The new wireless sensor company that has been making wireless security products for 30+ years.

Proven Security Innovation - Continuous Product Improvement has resulted in 9 U.S. Patents and ground-breaking development of encrypted security systems.

Trusted Engineering and Development Partner - MaxOut™ Technology is the company behind many of the security products used for residential, commercial, and high security today.

Door / Window Sensor – Mini

- Signals: supervisory, tamper, and low battery
- Case tamper
- Effective with vertical or horizontal mount - even on steel surfaces
- Two replaceable extra long-life Lithium batteries

319.5 MHz: # RFCMDWS319NN
Replaces: Interlogix: 60-362N-10-319.5
345 MHz: # RFCMDWS345NN
Replaces: Honeywell 5818MNL
 2.15 x 1 x .5 in.



Door / Window Sensor – Mini Extended

- An external contact can be connected to the transmitter through housing
- Signals: supervisory, tamper, and low battery
- Effective with vertical or horizontal mount - even on steel surfaces
- Two replaceable extra long-life Lithium batteries

319.5 MHz: # RFCMDWSX319NN
345 MHz: # RFCMDWSX345NN
 2.75 x 1 x .5 in.



Recessed Door / Window Sensor – Mini

- New, high-powered microprocessor, exceptional range-no dead spots
- Small, narrow switch package
- Exceptional RF performance
- Replaceable extra long-life lithium battery

319.5 MHz: # RFRDWS319NN
Replaces: UTC-GE-Sentrol-R1125T-N
345 MHz: # RFRDWS345NN
Replaces: Honeywell 5818MNL
 2.15 x .75 in.



Total Window Sensor

- Dual protection; contact open and on impact
- LED activation on impact —Turns off on restore
- Superior RF performance—even on steel

319.5 MHz: # RFSHK319NN
Replaces: UTC-GE-Sentrol-5414W
345 MHz: # RFSHK345NN
 2.35 x 1 x .5 in.



Extreme Sensor

- Supervised; detects opening and closing
- Tough, thick case with remote terminal
- Water-tight gasket seals out weather. Tested down to -35°F
- Superior RF performance—even on steel

319.5 MHz: # RFCMDWSOD319NN
345 MHz: # RFCMDWSOD345NN
Replaces: Honeywell 5816OD
 Sensor: 3.4 x 1.25 x 1 in.
 Magnet: 3 x .75 x .75 in.



Glass Break Detector

- Audio-style detector updated to today's standards
- Signals: supervisory, tamper, and low battery
- Two replaceable extra long-life Lithium battery

319.5 MHz: # RFARGB319NN
Replaces: UTC-GE-Sentrol-5600W
 3.88 x 2.75 x 1.42 in.



Rate-Of-Rise / Heat Detector – Mini

- Electronic processing to detect and report rising heat conditions
- Fixed temperature; 135°F (57°C) or 200°F (93°C), depending on the model
- Ceiling mount with small footprint, tamper switch
- Replaceable extra long-life Lithium battery

319.5 MHz: # RFROR135S319NN
345 MHz: # RFROR135S345NN
 2.25 x 1.5 in.



Smoke/ Heat Detector

- "Intelligent" alarm memory feature
- Replaceable extra long-life batteries
- Automatic dust compensation
- Integrated piezoelectric sounder. Large test/silence button

345 MHz: # RFAPSMK545NN
Replaces: Honeywell 5806W3
 4.75 x 1.25 in.



CO Detector

- Electrochemical 10 year CO sensor
- Audible and visual "End of Life" indication. Test/Hush button and Memory feature
- Integrated piezoelectric sounder
- Replaceable extra long-life Lithium battery

345 MHz: # RFAPCO345NN
Replaces: Honeywell 5800CO

4.7 x 4.13 x 1.5 in.



Combination Smoke/Heat/CO Detector

- Photoelectric smoke detector, thermistor heat detector, and electrochemical CO detector
- End of Life" indicator and Hush button feature
- Wireless signals; alarm, tamper, and low battery
- Two replaceable extra long-life Lithium batteries

345 MHz: # RFAPCMB345NN
Replaces: Honeywell 5800COMBO

.7 x 4.13 x 1.5 in.



PIR-Wall Mount

- Dual-element detector element with 80 lb. pet immunity
- Wall and cover tamper
- 40' Field-of-View range
- Extra long-life Lithium battery

319.5 MHz: # RFARPIR319NN
Replaces: UTC-GE-Sentrol-RCR50

345 MHz: # RFARPIR345NN
Replaces: Honeywell 5800PIR

4.25 x 2.25 x 1.75 in.



PIR-Ceiling Mounted – Mini

- Panoramic, 360° coverage
- Advanced, sensitive Micro-processor for superior detection and signal
- Wall tamper
- Two replaceable extra long-life Lithium batteries

319.5 MHz: # RFCPIR319NN
Replaces: UTC-GE-Sentrol-AP669

345 MHz: # RFCPIR345NN

3 x 1. in.



Water Sensor

- Detects as little as 1/32" of water
- Patented antenna for superior range
- Two replaceable extra long-life Lithium batteries

319.5 MHz: # RFWATER319NN

Transmitter: 2.5 x 1 x 1.5 in.
Sensor: 1.77 x .7 x .4 in.



Keyfob Control

- Arm-Away Mode - all devices active | Arm-Stay Mode - interior devices
- Panic Activation | Activate Lights - if control panel supports
- Auxiliary Out (requires panel features)
- Replaceable extra long-life Lithium battery

319.5 MHz: # RFKEYFOB319NN
Replaces: UTC-GE-Sentrol 600-1064-95r

2.32 x 1.5 x .5 in.



Keyfob Panic

- Wireless, portable panic/alert
- Signal on; push/push or push and hold
- Includes lanyard
- Replaceable extra long-life Lithium battery

319.5 MHz: # RFFOBPANIC319NN
345 MHz: # RFFOBPANIC345NN

2.32 x 1.5 x .5 in.



Long-Range Panic

- Powerful with exceptional range
- Signal on; 2-second hold or 2 short presses
- Includes; belt clip, desk mount, and lanyard clip
- Replaceable extra long-life Lithium battery

319.5 MHz: # RFPANICONEBUTTON319NN

3 x 2 x .7 in.



Enclosure Tamper Switch

- To protect security systems enclosures from removal or tamper
- Adjustable plunger for different gap sizes
- Reed actuated
- Closed-Loop with built-in service shunt

ACCTSHS KIT
Replaces Sentrol 3023 Tamper Switch

2 x 1 x 6/8 in.

